


B15T-7 Plus / B18T-7 Plus / B20T-7 Plus B16X-7 Plus / B18X-7 Plus / B20X-7 Plus B25X-7 Plus / B30X-7 Plus / B35X-7 Plus

7-SERIES PLUS FORKLIFTS

Electric 1.5 to 3.5 tonne capacity

3- and 4-wheel



7-Series Plus Electric Forklifts

The Doosan 3 and 4-wheel electric counterbalance forklifts provide great power, excellent performance, enhanced safety, driving comfort, outstanding serviceability and reliability.

MAXIMUM PRODUCTIVITY

Smaller turning radius

High visibility design

Convenient side battery removal system

Powerful traction and pump motor system

SAFETY

Large panoramic mirror

LED lights

Blue safety light

Fence light (optional)

Emergency switch Seat belt interlock

Guardian Stability System (GSS):

- Turtle mode
- Unlimited ramp hold
- Low battery alarm
- Mast Lowering Inter-Lock & Tilt Lock (ISO3691)
- Operator sensing system (OSS)
- Curve control speed





OPTIMAL ERGONOMICS

Finger tip controls (optional)
Adjustable steering column
Adjustable seat
Reduced noise level

EXCELLENT RELIABILITY

Reliable operation

Improved cooling performance

GREAT SERVICEABILITY

Worldwide service network

Doosan genuine parts

Easy-access all main components





Increased steer angle reduces the steering radius which allows you to maximise the most efficient warehouse lay-out to compliment your operation.





Side battery removal

The battery changing system (Side Roll In/Out or Side Lift In/Out) makes it easier and faster to exchange the battery. This allows multi-shift operation.



Excellent visibility

The re-designed overhead guard profile with angled roof bars provides a clear upward view whilst ensuring ultimate strength for safety. The excellent visibility enables you to work faster and more efficient. The ergonomic design of the operator compartment makes working fast and safe a pleasure. New features such as the increased length of the entry bar and the new accessory bar offer more comfort.

Safety



Unlimited ramp hold (Auto parking brake)

Ramp hold ensures the vehicle stays stationary no matter where it is positioned; and will only move when required by the operator



Drive speed control

Based on the lifting height, other speeds (travel/lift) are also reduced to make the forklift even safer.



Auto parking brake (EPB)

The parking brake automatically activates with no physical switch when the driver leaves the seat to ensure safety around the vehicle.



Mast Lowering Interlock & Tilt Lock (ISO3691)

When the operator leaves the truck unattended, the hydraulic locking system prevents unintentional lowering and tilting of the mast. It safeguards the truck, the load and the work array.



Electric foot brake system (EFB)



The brake starts when you release your foot from the accelerator pedal. This technology has been extended to the service brake system.



OPTION

Fence light



A warning is given to pedestrians by reflecting red lines around the vehicle. Front and rear safety lights are also available.






Mast oscillation control

You can work and drive safer even when the mast is raised to its maximum height. The improved design provides better control of mast oscillation, which stops abruptly after the initial short period of movement. The drive speed is controlled by the mast height (STD). The vehicle's max speed will reduce by 50% for safety reasons. (GSS option is built in as STD).

NEW

-43% when tilting* 3% when side shifting*

comparison with BT/BX 7-Series







Adjustable steering column

The operator can change the stepless adjustable column to the best position that provides convenience and comfort.



Adjustable seat **OPTION**

The newly improved design offers upgraded features:
Low-vibraton seat: absorbing shocks, full suspension up to 150 kg, adjustable

- Improved suspension
- Improved endurence
- Increased convenience:
 Operation is now easier due to the increased size of the armrest control lever.
- Ease of Maintenance: Parts can now be exchanged without removing the seat from the vehicle.

Turtle mode

By pushing the turtle mode button when the truck operates in a confined space, the truck travel speed will slow down to a predefined travel speed setting, without impacting the lifting speed. This mode ensures safe manoeuvring in delicate operating situations.



LED lights

Brighter and longer lasting than traditional sealed beams or halogen lights.



Blue safety light **OPTION**

The blue safety light warns oncoming forklifts or pedestrians by projecting a blue light on the floor. This helps prevent accidents in the workplace.

Great serviceability & Excellent reliability



Improved water protection package



Protection against water and dirt for outdoor use has been improved. The front cover increases protection to the drive motor area. Belly plate option reduces any risk of contaminates entering from underneath the truck. All electrical connectors are IP67 rated, allowing better dust and moisture protection.

Reliable Operation

Curtis AC controllers provide an unbeatable combination of power, performance and functionality. They are very reliable and well proven.



IP43 dust and water protection drive and pump


The new sealed controllers are rated to IP65 and the enclosed motors are rated to IP43.















Main Specifications

MAJOR SPECIFICATION		B15T-7 Plus	B18T-7 Plus	B20T-7 Plus	
Classification		3-wheel electric			
Capacity	kg	1,500	1,750	2,000	
Load center	mm	500			
Wheel base	mm	1,323	1,423	1,446	
Turning radius	mm	1,515	1,615	1,648	
Load distance: center of drive axle to fork	mm	376	376	381	
Travel speed loaded/unloaded	km/h	17/17	17/17	17/17	
Lift speed loaded/unloaded	mm/s	400/600	400/600	400/600	
Lowering speed loaded/unloaded	mm/s	500/450	500/450	500/450	
Max. gradeability (at 1.6km/h, loaded)	%	26	25	24	
Max. drawbar pull (loaded)	N	12,749	12,749	12,749	
Aisle width for pallets 1.000 X 1,200 crossways	mm	3,216	3,316	3,354	
Aisle width for pallets 800 X 1.200 lengthways	mm	3,341	3,441	3,479	
S/A Steering angle	o	90	90	90	

Standard Features and Options

SAFETY & STABILITY, GUARDIAN STABILITY SYSTEM (GSS)

Guardian Stability System (GSS)

- OSS (Operator Sensing System)
- Neutral position for start
- Unlimited slope hold
- Curve control speed
- Low battery warning alarm
- Seat belt indicator
- Mast lowering interlock & tilt lock (ISO 3691)
- Decrease of travel speed (up to 50%) when the mast is raised above the primary stage

Easy entry grab bar

Electro-magnetic automatic parking brake (EPB)

Electric foot brake system (EFB)

Mast sway & drive speed control

LED lights

Emergency stop switch

Auto tilt leveling

Fence light

Panoramic mirror

Additional options for GSS:

- Forward tilt is reduced by 2° when the mast is raised above the primary stage
- Alarm sounds when the mast is raised above the primary stage with the mast tilted more than 2°

ERGONOMICS

Laura auto, atau with auti aliu wattam	
Large entry step with anti-slip pattern	
Large & angled floor plate (leg room) with rubber cushion	
Rounded design battery hood cover	
Easy to read instrument panel	
Adjustable tilt steering column & easy grip (Ø 280 size) steering wheel	
Hydraulic control lever with direction switch	
Large cup holder, usb port & 12V electric jack, clip board	
Additional accessory bar	
Reduced noise level	
Rear grab bar with horn	
Steering wheel with knob	
Fingertip	
Newly improved adjustable seats	
Special height overhead guards	
Mono pedal	
Modular cabins	

Standard featuresOptions

B16X-7 Plus	B18X-7 Plus	B20X-7 Plus	B25X-7 Plus	B30X-7 Plus	B35X-7 Plus	
4-wheel electric						
1,600	1,800	2,000	2,500	3,000	3,500	
	500					
1,495	1,495	1,495	1,589	1,734	1,750	
1,886	1,886	1,886	1,950	2,095	2,155	
376	376	381	448	454	454	
17/17	17/17	17/17	16/18	16/18	16/18	
400/600	400/600	400/600	480/600	420/600	380/600	
500/450	500/450	500/450	490/460	490/460	500/460	
26	25	24	25	22	20	
12,749	12,749	12,749	17,338	17,338	17,338	
3,466	3,466	3,471	3,620	3,772	3,832	
3,662	3,662	3,667	3,799	3,950	4,010	
86	86	86	93	93	93	

PRODUCTIVITY

Full AC system chassis	
Rounded design counterweight	
86° (BX)/ 90° (BT) Steering angle	
Hydraulic cushioned valve in freelift cylinder (FFL & FFT)	
Battery lift/roll in and out system	
Cooling options: Fans & Fin type controller	

RELIABILITY

Robust frame structure & strong structure overhead guard	
IP65 Rated Curtis controller	
IP43 Rated PAL enclosed type motors	
Improved cooling performance	
Controller cover	
Belly plate	

SERVICEABILITY

Easy to access controller & motors room	
Wide open battery hood cover	
Durable heat-resisting (38"SQ) cables	
Tool-less side cover with air ventilation	
Easy View	

This list is based on factory data. Standard or optional can vary for specific countries.



- Production Subsidiary
- Sales Subsidiary
- Parts Depot Center

B20TX-B25X-7 PLUS-210719V1EN (July 2021)

Authorized Dealer



Doosan Industrial Vehicle UK 12 Kilvey Road Brackmills Industrial Estate Northampton NN47BQ

Tel.: 01604 825 600 Website : www.doosanflt.com









